

آذران ماشین



GREEN LIGHT TO USE
WHEN YOU LIKE

Small Traction
Solutions
Hawker XFC™

EnerSys
Power/Full Solutions



Power: Just in Time

When you are not using it, charge it!



Transform the way of work – forever!

The new Hawker® XFC™ batteries will revolutionise the way you work. Designed using advanced Thin Plate Pure Lead Technology providing increased energy density and fast charge acceptance. Hawker XFC batteries with matched EnerSys® HF charger can be used as and when required: use them as you want, and recharge whenever you can, during breaks and at the end of the shift.

Very rapid recharge

The battery can even be put back into service before it is fully recharged.

Unlike conventional lead/acid batteries where you discharge to a specified level and then need to recharge for 8-12 hours, Hawker XFC is totally flexible giving increased autonomy to you.

New construction


Advanced technology and robust construction delivering exceptional performance. Hawker XFC batteries are maintenance free. The electrolyte is absorbed in a superior quality microporous glass mat separator with high absorption and stability designed to enhance cyclic capability. Positive and negative plates are low impedance, high corrosion resistant thin plate grids (pure lead)

manufactured using a unique process. Containers are ABS, highly resistant to shock and vibration.

Many applications

These batteries are suitable for use in small traction applications such as:

- Pallet trucks
- Floor care (cleaning machines)
- Shuttle personnel carriers
- Industrial utility vehicles (small refuse collection vehicles for example)
- And many other applications



Totally revolutionary

The specific charging profile developed for recharging the Hawker® XFC™ allows a rapid recharge in less than 4 hours at 60% DOD and opportunity charging as often as needed without damaging the batteries.



A wide spectrum of high-lights

The new Hawker XFC has been designed optimising cycling performance as well as reducing the recharge time when combined with our approved charger. The state-of-the-art technology of these batteries allows superior performance and a long list of benefits compared to conventional lead acid batteries (gel or flooded).

Customer benefits

- Opportunity charge whenever the truck is not being used, can eliminate the need for spare batteries & battery changing
- Short recharge time (less than 4 hours) at 60% DOD, with approved charger)
- Suitable for multi-shift operations and optimises machine availability
- Totally maintenance-free, no topping-up
- 'Green' - reduced carbon footprint due to very low charge factor
- Reduced electricity costs for recharging due to very low charge factor
- Space saving: Hawker XFC typically occupies 30% less space than an equivalent capacity battery of conventional design = more power for less space
- Excellent cycle life (up to 1,200 cycles at 60% DOD)
- High energy throughput (up to 160% of C_5 per 24 hours-maximum DOD of 80% must be observed, please ask for further details for this application)
- Environmentally friendly
- Minimum gassing: ideal for use in shops, public areas and sensitive manufacturing areas
- Hawker XFC is available in single 12 V units or assembled batteries to suit various applications: pallet trucks, floor care, personnel and industrial electric trucks
- Easy installation in any orientation except inverted
- Highly recyclable

Technical Data

Type	Voltage [V]	Nominal Capacity [Ah] C ₅	Nominal Capacity [Ah] C ₂₀	Dimensions [mm]				Weight* [kg]	Terminal	Terminal adapter	Terminal Layout
				L	W	Box Ht	Term. Ht				
12XFC25	12	25	29	250	97	147	144	9.6	M6 Female	SAE post	1
12XFC35	12	35	41	250	97	197	194	13.2	M6 Female	SAE post	1
12XFC48	12	48	54	220	121	252	248	18.7	M6 Female	SAE post	1
12XFC58	12	58	64	280	97	264	248	19.1	M8 Female	not applicable	2
12XFC60	12	60	63	329	166	174	166	24.2	M6 Female	SAE post	1
12XFC82	12	82	98	395	105	264	248	27.2	M8 Female	not applicable	2
12XFC158	12	158	179	561	125	283	263	51.5	M8 Female	M6 Male front terminal	2
12XFC177	12	177	202	561	125	317	297	59.6	M8 Female	M6 Male front terminal	2

* +/-3%

Terminal Layout

Layout 1



Layout 2



General Specifications

24 V 158 Ah battery (1):

- Battery crate dimensions - 621 mm x 146 mm x 627 mm or 621 mm x 209 mm x 627 mm high
- Standard battery connector - Rema 80 A

Available as original equipment or replacement with matched charger

24 V 316 Ah battery (2):

- Battery crate dimensions - 621 mm x 281 mm x 627 mm high
- Standard battery connector - Rema 160 A (160 A to 80 A adaptor lead available as an option)

Available as original equipment or replacement with matched charger



(1)



(2)

The designated charging rate for Hawker® XFC™ is between 0.4 C₅ and 0.7 C₅ giving optimum performance, recharge time and cycle life.

Other ratings can be used with the agreement of EnerSys® Technical.

Authority - please consult your local EnerSys Application Engineer for details.

For further details refer to Technical Data Hawker Lifetech XFC™.

Hawker® XFC™ ... a step into the future of battery technology!



European Headquarters:

EnerSys EMEA
EH Europe GmbH
Löwenstrasse 32
8001 Zürich
Switzerland
Phone: +41 44 215 74 10
Fax: +41 44 215 74 11

Local contact:

EnerSys Ltd
Oak Court
Clifton Business Park
Wynne Avenue
Swinton
Manchester M27 8FF
Phone: 0161 794 4611
Fax: 0161 727 3809

Please refer to the website address for details of your nearest EnerSys office:
www.enersys-emea.com

© 2012. All rights reserved. All trademarks and logos are the property of or licensed to EnerSys and its affiliates unless otherwise noted.